

WINTEX 1000

Accuracy and speed

WintexAgro

Precision Farming Starts Here.



All soil types



Driver's seat operation



GPS enabled



Electronic depth control



Single soil box

Wintex Agro

Vilhelmsborgvej 8C, DK-7700 Thisted
+45 97990800, contact@wintexagro.com
wintexagro.com



Precision Farming Starts Here.

MORE SAMPLES. LESS TIME.

Capture a true picture of your topsoil's nutrient level with an infinitely adjustable sampling depth up to 25 cm in 4 seconds. Make a long day of soil sampling less tiring by comfortably controlling all functions from the driver's seat.

- Homogeneous samples - a **true picture of the soil's health**
- Accurate samples in all soil types - even in extremely dry, freshly tilled, or wet soils
- Adjust the depth of the probe infinitely and conveniently on a monitor, which ensures **consistent sampling depth**.
- The **WINTEX 1000** integrates with your existing GPS unit to **automatically georeference** all samples, making repeatable, year-to-year sampling seamless and simple. Use the data to create precise fertility and fertilizer prescription maps to **increase productivity in your fields**.



TECHNICAL SPECIFICATION

Depth:	0-25 cm
Layers:	1
Diameter probe:	18 or 21 mm
Driven by:	electric motor, hydraulic cylinder
Sampling speed:	4 sec.
Engine:	Honda GX160, 4.8 hp
Electric starter:	optional
Net weight unit:	48.5 kg

Volume/sample at a density 1:1:

18 mm probe: 1.4 g/cm; 21 mm probe: 2.2 g/cm

THE WINTEX CONTROL SYSTEM



Take control with ease - the **WINTEX control system** lets you adjust settings, enter presets, and manage every function effortlessly from one intuitive interface.

MOUNTING OPTIONS

UTV: side or back

ATV: side or back

Pickup

Tractor, three-point hitch

Wintex Agro

Vilhelmsborgvej 8C, DK-7700 Thisted
+45 97990800, contact@wintexagro.com
wintexagro.com

